



Connecticut Precast Corp.

555 Fan Hill Road, Monroe, CT 06468

Telephone (203) 268-8688

Fax (203) 452-1007

Septic Tanks

LIQUID CAPACITY	Length L	Width W	Invert I	Height H	Sections
3000	16'-0"	7'-0"	4'-5"	5'-10"	2
3500	16'-0"	7'-0"	5'-0"	6'-5"	3
4000	16'-0"	7'-0"	5'-7"	7'-0"	3
4500	16'-0"	7'-0"	6'-2"	7'-7"	3
5000	16'-0"	7'-0"	6'-9"	8'-2"	3
5500	16'-0"	7'-0"	7'-4"	8'-9"	4
6000	16'-0"	7'-0"	7'-11"	9'-4"	4
6500	16'-0"	7'-0"	8'-6"	9'-11"	4
7000	16'-0"	7'-0"	9'-1"	10'-6"	4
7500	16'-0"	7'-0"	9'-9"	11'-2"	5

3,000 - 7,500 Gallon Capacity
Commercial

Design Notes:

1. Concrete - 4,000 PSI @ 28 DAYS
2. Meets or exceeds state and local requirements.
3. All shiplap joints sealed with Butyl Rubber.
4. Design Loading: AASHTO HS-20.
5. Two compartment tank.
6. Side inlet pipes shall extended to cleanout cover thru cast in pipe support.
7. Maximum fill over top of tank - 3 feet.
8. Tank shall be supplied with 4" dia. tees and biofilter.

