



NOTES:

- 1) SAFETY EXTENSION DEVICE MUST BE PROPERLY INSTALLED BY QUALIFIED PERSONNEL. POST SHALL BE MOUNTED ON THE WALL SIDE OF THE LADDER.
- 2) THE STAINLESS STEEL LOCK PIN MUST BE SECURELY SEATED IN RECEIVING SLOT BEFORE PROCEEDING TO USE SAFETY DEVICE.
- 3) SAFETY EXTENSION DEVICE WILL EXTEND 42" ABOVE THE TOP OF THE TUBE GUIDE.

THIS DOCUMENT IS THE PROPRIETARY PROPERTY OF SYRACUSE CASTINGS. IT HAS BEEN FURNISHED UPON THE CONDITION THAT IT SHALL NOT BE RELEASED, DUPLICATED, USED, OR DISCLOSED IN WHOLE OR IN PART FOR ANY PURPOSE WITHOUT THE EXPRESS WRITTEN PERMISSION OF SYRACUSE CASTINGS AND SHALL BE CONSIDERED CONFIDENTIAL INFORMATION.

ALUMINUM SAFETY EXTENSION DEVICE

DRAWING # SAFETY POST

Drawn By: C.M.A. DATE: 05/22/98 Revised By: ARO Revised: 08/22/02

Syracuse Castings P.O. Box 1821
 6177 South Boy Rd.
 Cicero, N.Y. 13039
Better By Design

Phone # 315-699-2601 Fax # 315-699-2982 www.syrccst.com