

 **A•LOK® PRODUCTS, INCORPORATED**  
**DIMENSIONAL DATA SHEET**

A•LOK® Ring NO.	Nominal Pipe O.D. ± 0.25"	Ring Dia. --- A•LOK® I.D.	<b>USE AS A GUIDE ONLY</b> <b>CHECK PIPE O.D. WITH MANUFACTURE</b> <b>PIPE TYPES</b>
*140	4.25"	3.25"	4" PVC (SDR 35), (D 3034)
*150	4.50"	3.50"	4" PVC (SDR 21), (SDR 26) (SDR 40), (A-2000)
*160	4.75"	3.75"	4" PVC (SDR 25); 4" DUCTILE IRON (DI)
*165	5.00"	4.00"	4" VITRIFIED CLAY (VC)
*170	5.25"	4.25"	4" (VC)
*200	6.25"	5.25"	6" PVC (SDR 35), (SDR 41), (D 3034)
*210	6.50"	5.50"	6" PVC (SDR 21), (SDR 26), (SDR 40)
*225	6.875"	5.875"	6" DI, 6" PVC (A-2000), 6" PVC (SDR 25), 6" TRUSS
*235	7.25"	6.25"	6" VC
240	7.50"	6.50"	6" VC
255	7.82"	6.82"	6" VC
*285	8.50"	7.00"	8" PVC (SDR 35), (SDR 41), (SDR 26), (SDR 21), (SDR 40), (D 3034)
*300	9.00"	7.50"	8" DI, 8" PVC (SDR 25)
*310	9.25"	7.75"	8" TRUSS, 8" PVC (A-2000)
*320	9.50"	8.00"	8" VC, 8" TRUSS
325	9.75"	8.25"	8" VC
330	10.00"	8.50"	8" VC
340	10.25"	8.75"	8" REINFORCED CONCRETE (RC)
*350	10.50"	9.00"	10" PVC (SDR 35), (SDR 41), (SDR 21), (D3034)
355	10.75"	9.25"	10" SPECIAL
*370	11.25"	9.75"	10" DI, 10" PVC (SDR 25)
380	11.50"	10.00"	10" PVC (A-2000)
*385	11.75"	10.25"	10" TRUSS
390	12.00"	10.50"	10" VC
400	12.25"	10.75"	10" VC
*410	12.50"	11.00"	12" PVC (SDR 35), (SDR 41), (SDR 21), (D 3034)
415	12.75"	11.25"	12" SPECIAL
*425	13.00"	11.50"	12" DI, 12" PVC (SDR 25)
440	13.25"	11.75"	12" A-2000
455	14.00"	12.50"	12" TRUSS
470	14.25"	12.75"	12" VC
475	14.375"	12.825"	12" VC
480	14.75"	13.25"	12" VC

**\* MOLDED GASKETS AVAILABLE**

MARCH 1, 2000—SUPERSEDES ALL PREVIOUS INFORMATION AND IS SUBJECT TO CHANGE WITHOUT NOTICE.  
ALL DIMENSIONS ARE SUBJECT TO MANUFACTURES TOLERANCES.

**IMPORTANT -- TYPE OF PIPE OUTSIDE DIAMETERS REQUIRED WHEN ORDERING A•LOK® CONNECTORS AND EQUIPMENT.**

 **A•LOK® PRODUCTS, INCORPORATED**  
**DIMENSIONAL DATA SHEET**

A•LOK® RING NO.	NOM. PIPE O.D. ± 0.25"	RING DIA. --- A•LOK® I.D.	USE AS A GUIDE ONLY CHECK PIPE O.D. WITH MANUFACTURE PIPE TYPES
490	15.25"	13.75"	14" DI, 15" PVC (SDR 35), (SDR 41), (D3034)
500	15.50"	14.00"	15" SPECIAL
520	16.00"	14.50"	12" RC'B
525	16.25"	14.75"	12" SPECIAL
540	16.25"	14.75"	12" SPECIAL
570	17.50"	16.00"	12" RC'C, 15" TRUSS, 16" DI
580	18.00"	16.50"	15" VC, 16" (PSCP) Type B, 18" Steel
600	18.50"	17.00"	15" VC
610	18.75"	17.25"	18" TRUSS, 18" PVC (F679)
620	19.125"	17.625"	18" PVC (F794)
630	19.50"	18.00"	15" RC'B, 18" DI
640	20.00"	18.50"	15" RC, 20" STEEL
650	20.25"	18.75"	18" (PSCP) TYPE B
675	21.00"	19.50"	15" RC'C, 18" VC
690	21.375"	19.875"	20" DI
700	21.437"	19.937"	18" VC
710	22.00"	20.50"	18" VC, 21" PVC (F679), 20" (PSCP)
720	22.50"	21.00"	21" PVC (F794)
740	23.00"	21.50"	18" RC'B
750	23.50"	22.00"	21" SPECIAL
770	24.00"	22.50"	24" STEEL
780	24.50"	23.00"	18" RC'C
800	24.75"	23.25"	24" PVC (F679)
805	25.00"	23.50"	18" RC'(C+ 0.25"), 24" PVC
815	25.50"	24.00"	24" PVC (F794)
820	25.75"	24.25"	24" DI
840	26.00"	24.50"	21" VC
850	26.50"	25.00"	21" RC'B
855	26.75"	25.25"	24" A-2000
860	27.00"	25.50"	24" (PSCP) TYPE B
890	28.00"	26.50"	21" RC'C, 27 PVC (F679)
900	28.25"	26.75"	21" RC (SPECIAL)
915	28.50"	27.00"	24" VC
920	28.75"	27.25"	27" PVC (F794)
930	29.00"	27.50"	24" VC

MARCH 1, 2000—SUPERSEDES ALL PREVIOUS INFORMATION AND IS SUBJECT TO CHANGE WITHOUT NOTICE.  
ALL DIMENSIONS ARE SUBJECT TO MANUFACTURES TOLERANCES.

**IMPORTANT -- TYPE OF PIPE OUTSIDE DIAMETERS REQUIRED WHEN ORDERING A•LOK® CONNECTORS AND EQUIPMENT.**

 **A•LOK® PRODUCTS, INCORPORATED**  
**DIMENSIONAL DATA SHEET**

A•LOK® Ring NO.	NOM. PIPE O.D. ± 0.25"	RING DIA. --- A•LOK® I.D.	USE AS A GUIDE ONLY CHECK PIPE O.D. WITH MANUFACTURE PIPE TYPES
970	30.00"	28.00"	24" RC'B
980	30.50"	28.50"	24" SPECIAL
1000	30.75"	28.75"	24" RC (B + 0.375")
1020	31.25"	29.25"	30" PVC
1030	31.50"	29.50"	24" RC'C
1035	31.625"	29.625"	24" SPECIAL
1040	32.00"	30.00"	30" PVC (F794), 30" DI
1050	32.375"	30.375"	27" VC
1070	32.875"	30.875"	24" RC (C + 0.750")
1090	33.50"	31.50"	27" RC'B
1100	33.80"	31.75"	30" PVC (A-2000)
1110	34.25"	32.25"	27" RC (B + 0.375")
1130	35.00"	33.00"	27" RC'C
1140	35.25"	33.25"	27" RC; 33" PVC (F679)
1160	35.75"	33.75"	30" SP 5
1200	37.00"	35.00"	30" RC'B
1210	37.50"	35.50"	30" RC (B + 0.25")
1220	37.70"	35.70"	36" PVC
1230	38.00"	36.00"	30" RC (B + 0.50")
1235	38.375"	36.375"	36" PVC (F794)
1240	38.50"	36.50"	30" RC'C, 36" DI
1250	38.75"	36.75"	30" RC
1260	39.00"	37.00"	30" RC (C + 0.25"); 36" PVC (F679)
1280	39.50"	37.50"	30" RC
1310	40.50"	38.50"	33" RC'B, 36" (PSCP) Type B
1320	40.75"	38.75"	36" PSCP
1330	41.125"	39.125"	36" SP
1350	42.00"	40.00"	33" RC'C
1360	42.25"	40.25"	33" RC'(C + 0.25")
1370	42.50"	40.50"	36" SP 5
1390	43.25"	41.25"	42" FIBERGLASS
1420	44.00"	42.00"	36" RC'B, 42" PVC
1430	44.50"	42.50"	42" DI
1470	45.50"	43.50"	36" RC'C

MARCH 1, 2000—SUPERSEDES ALL PREVIOUS INFORMATION AND IS SUBJECT TO CHANGE WITHOUT NOTICE.  
ALL DIMENSIONS ARE SUBJECT TO MANUFACTURES TOLERANCES.

**IMPORTANT -- TYPE OF PIPE OUTSIDE DIAMETERS REQUIRED WHEN ORDERING A•LOK® CONNECTORS AND EQUIPMENT.**

 **A•LOK® PRODUCTS, INCORPORATED**  
**DIMENSIONAL DATA SHEET**

A•LOK® Ring NO.	NOM. PIPE O.D. ± 0.25"	RING DIA. --- A•LOK® I.D.	USE AS A GUIDE ONLY CHECK PIPE O.D. WITH MANUFACTURE PIPE TYPES
1475	45.75"	43.75"	36" NEPTUNE
1480	46.00"	44.00"	36" RC
1520	47.25"	45.25"	42"(PSCP) TYPE B
1530	47.50"	45.50"	Special PVC
1540	48.00"	46.00"	36" RC (SPECIAL)
1570	49.00"	47.00"	42" RC (SPECIAL)
1625	50.50"	48.50"	48" PVC
1670	52.00"	50.00"	42" RC (SPECIAL)
1690	52.50"	50.50"	42" RC'C
1700	52.75"	50.75"	42" RC (SPECIAL)
1705	53.00"	51.00"	42" RC (SPECIAL)
1710	54.00"	52.00"	48" (PSCP) Type B
1745	54.50"	52.50"	48" SPECIAL
1790	56.00"	54.00"	42" RC (SPECIAL)
1820	56.875"	54.875"	54" DI
1830	57.00"	55.00"	54" FIBERGLASS
1840	57.50"	55.50"	54" DI
1860	58.00"	56.00"	48" RC'B
1910	59.50"	57.50"	48" RC'C
1920	60.00"	57.50"	48" RC SPECAIL
1930	61.50"	59.00"	60" DI
1940	62.00"	59.50"	54" PSCP
1970	63.00"	60.50"	60" FIBERGLASS, 60" PRESSURE PIPE
2040	65.00"	62.50"	54" RC'B
2080	66.50"	64.00"	54" RC'C
2140	67.00"	64.50"	64" RC (SPECIAL)
2300	72.00"	69.50"	60" RC'B
2360	73.50"	71.00"	60" RC'C
2560	80.50"	78.00"	66" RC'C
2750	86.25"	83.75"	72" RC'(B + 0.25")
2800	87.50"	85.00"	72" RC'C

MARCH 1, 2000—SUPERSEDES ALL PREVIOUS INFORMATION AND IS SUBJECT TO CHANGE WITHOUT NOTICE.  
ALL DIMENSIONS ARE SUBJECT TO MANUFACTURES TOLERANCES.

**IMPORTANT -- TYPE OF PIPE OUTSIDE DIAMETERS REQUIRED WHEN ORDERING A•LOK® CONNECTORS AND EQUIPMENT.**