

BAY OIL COMPANY

38 PAINFIELD STREET
CHICOPEE, MA 01013

TEL. (413) 737-7728

AQUA-SAFE Concrete Sealer Waterproofing Concrete Sealer

Description

AQUA-SAFE is a ready to use, solvent free, semi-mastic, water base water proofing sealer for all concrete above and below ground surfaces

Benefits

- VOC Compliant
- Easy clean up with water
- Non Flammable- no fire risk
- Dries quickly
- Bonds with damp or green concrete or green concrete

Surface Preparation

All surfaces must be free of oil, grease, rust scale, loose paint and dirt.

Application

AQUA-SAFE should be mixed well. Apply with roller, brush or suitable sprayer. Coating will depend on condition or porosity of surfaces. Approximately 1 gallon per 200 sq. ft. Temperature above 50 degrees Fahrenheit.

Clean up

Fresh coating can be removed with water. Kerosene or mineral spirits if coating has started to dry. Keep application in water.

Physical Properties

Weight per gallon 8.4-8.9 Ib.
Typical solids 45% wt.
Coverage approximately 2 gal/100 sq. ft.
Film Thickness 1/16" wet- depends on porosity
Non Flammable-wet
Solids approximately 45% Wet
Drying Time Touch - 4 hours

Regulatory Data

Volatile Organic Compound (VOC) - 0 gr./liter
HMIS rating H2,F-1,R-1, PP-X
RCRA Hazardous Substances-none
Sara Title III listing- RQ Value 100 Ib.

Compliance

ASTMD 1187 Type 1
ASTM D 1227 Type El class 1.

Shipping

5 gallon can
55 gallon drum
Bulk container

Caution

Keep from freezing

Note: See MSDS for further environmental information